

# **PEAK GOLD MINES**

# MONTHLY ENVIRONMENTAL MONITORING SUMMARY

# **July 2016**

Prepared By	Peak Gold Mines					
Signature	Jenna Marett					
Publish Date	8/08/2016					
Distribution	New Gold Internet					



# **Table of Contents**

INTEN	T:	3
SCOPE	<u>:</u>	3
DEFINI	TIONS:	3
MONI	TORING RESULTS:	4
	Vibration Monitoring Results:	4
	Air Quality Monitoring Results:	5
	Attended Noise Monitoring Results:	6
	Water Monitoring Results:	7
	Weather Data Results:	8



#### 1. INTENT

This monthly environmental summary report is a requirement under section 66(6) of the NSW *Protection of the Environment Operations Act 1997* (POEO Act), in which holders of an environment protection licence make their pollution monitoring data publicly available. This report is intended to keep the community, stakeholders, and regulators informed of Peak Gold Mine's (PGM's) environmental performance and to maintain a transparent and accountable reporting system.

#### 2. SCOPE

This report covers all of PGMs environmental monitoring conditions covered for July 2016. These conditions, where applicable, are measured against PGMs Environmental Protection Licence (EPL), development consent conditions and Australian Standard to determine PGMs compliance. The conditions include;

- Blasting monitoring results;
- Air Quality Monitoring results;
- Noise Monitoring results;
- Surface Water Monitoring results; and
- Weather Conditions.

#### 3. DEFINITIONS

mm/s - the peak of the vibration in millimetres per second

Insoluble Solids – the insoluble portion of the dust deposition

**Total Lead** – Including dissolved lead in the liquid portion and the lead particulates in the filter paper following laboratory analysis

g/m<sup>2</sup>/month – grams per square meter per month

**dB (L)** – decibel (linear maximum)

dB LAeq(15 minute) - Decibel (linear weighted average over 15 minutes)

**CN Free** – Free Cyanide (hydrogen cyanide and cyanide ions in solution)

CN WAD – Weak Acid Dissociable Cyanide (includes cyanide species liberated at moderate pH of 4.5)

TSS – Total Suspended Solids



#### 4. MONITORING RESULTS

## 4.1 Vibration Monitoring Results

The vibration monitoring results displayed in Table 4.1a represents all blast vibration events that were trigged at the New Occidental, Fort Bourke and/or Dellavale monitors. Full dataset for EPL licenced monitoring stations are located on <u>New Gold web page</u>.

As seen in Table 4.1a all blasting events for the month were below PGMs EPL limits. Vibration limits set by the NSW Environmental Protection Authority (EPA) can be viewed in Table 4.1b.

The compliance against the overall 12 month period will be reported in the EPL Annual Return and Annual Environmental Management Report (AEMR).

Table 4.1a New Occidental, Fort Bourke and Dellavale Vibration Results

Location	Date Sampled & Received	Blast ID	Development / Production	New Occidental (mm/s)	Fort Bourke (mm/s)	Dellavale (mm/s)	Complies (Y/N)
New Cobar	2/7/2016	9735StpMainN510	Production	No Trigger	2.85	4.68	Yes
New Cobar	4/7/2016	46StpMainN200	Production	No Trigger	2.86	1.13	Yes
New Cobar	7/7/2016	8790StpMainS645	Production	No Trigger	1.13	No Trigger	Yes
New Cobar	8/7/2016	63StpMainN365	Production	No Trigger	1.69	0.65	Yes
New Cobar	9/7/2016	9970StpEastS320	Production	No Trigger	1.03	2.51	Yes
New Cobar	10/7/2016	46StpMainN200	Production	No Trigger	3.8	1.05	Yes
New Cobar	16/7/2016	51StpCentS150	Production	No Trigger	2.09	1.4	Yes
New Cobar	17/7/2016	63StpMainN365	Production	No Trigger	1.3	0.58	Yes
New Cobar	20/7/2016	9970StpEastS320	Production	No Trigger	2.52	2.59	Yes
New Cobar	22/7/2016	63StpMainN365	Production	No Trigger	4.32	2.38	Yes

Table 4.1b PGMs EPL Limits for Vibration

Peak Particle Velocity (mm/s)	Allowable Exceedance
5.00	<5% of the total number of blasts in a 12 month period are to be below 5mm/s
10.00	NIL



## 4.2 Air Quality Monitoring Results

Fall out dust deposition bottles are currently used to monitor air quality. The bottles are positioned in the field for a period of  $30 \pm 2$  days. Monitoring is undertaken quarterly. The bottles are then sent to Australian Laboratory Services (ALS) for external analysis.

PGM has no set limits for air quality monitoring levels. However, takes on board the EPAs best practice limit of  $4g/m^2$ /time (limit is applicable to 12 month averaging period). If a single monitoring result is over the EPAs best practice limit of  $4g/m^2$ /time, the cause is investigated and reported in the AEMR.

No dust monitoring was undertaken during July.

Full dataset for EPL licenced monitoring stations are located on New Gold web page.



## 4.3 Attended Noise Monitoring Results

A hand held monitor is used by PGM employees to monitor noise levels at times set out by the EPL and development consent conditions. Noise monitoring is conducted at the closest resident and sporadically depending on operational requirements. PGMs closest monitoring point is located at the Dellavale boundary, approximately 400m closer to the mine noise than the residence. To determine the noise level (dB) experienced at the residence, sound intensity I and the inverse square law  $1/r^2$  is calculated based on the residences distance from mine noise source.

Noise monitoring results and licenced noise limits set by the EPL and Development Consent Conditions are given in Table 4.3a respectively.

Full dataset for EPL licenced monitoring stations are located on New Gold web page.

No noise monitoring was undertaken in July.

**Table 4.3a Attended Noise Monitoring Results** 

	Date			LA 10	LA 10 (dB) Monitoring	LA 10 (dB) Calculated		
Location	Sampled & Obtained	Published	Time	(dB) Limit	Result at Monitor Location	Monitoring Result at Residence	Key Noise Source	Complies

**Table 4.3a Attended Noise Monitoring Limits** 

Time Band	Day	Noise Level (dB)
8:00am – 6:00pm	Mon – Fri	45
6:00pm – 10:00pm	Mon – Fri	40
10:00pm – 8:00am	Mon – Fri	35
8:00am – 1:00pm	Sat	45
1.00pm – 8:00am	Sat	35
12:00am – 12:00pm	Sun	35



## 4.4 Water Monitoring Results

Surface water monitoring involves collecting water samples from a number of locations around site and submitted to external laboratory for physical and chemical analysis, pH and electrical conductivity are obtained using a handheld monitor. Table 4.4 gives the results as per the PGM EPL requirements.

Full dataset for EPL licenced monitoring stations are located on New Gold web page.

**Table 4.4 Surface Water Monitoring Results** 

Monitoring	Date				CN WAD	CN Free	Oil & Grease	TSS	Complies
Point	Sampled	Received	Published	Limit	mg/L	mg/L	mg/L	mg/L	
Spains Tank	22/07/2016	29/07/2016	2/08/2016	No Limit			<5	8	Yes
Tailings Decant Dam	25/07/2016	1/08/2016	2/08/2016	No Limit	0.509	0.327			Yes



#### 4.5 Weather Data Results

PGM meteorology monitoring data has been acquired through the Bureau of Meteorology (BOM) weather station located 2km North West of Cobar.

The **BOM** can be used as an alternate source for this monitoring data.









