

Peak Gold Mines MONTHLY ENVIRONMENTAL MONITORING SUMMARY REPORT

EPL 3596 Hillston Road, Cobar NSW 2835

August 2018



Contents

1. INTENT	3
2. SCOPE	3
3. DEFINITIONS	3
4. MONITORING RESULTS	4
4.1. VIBRATION	4
4.2. AIR QUALITY	5
4.3. NOISE	7
4.4. WATER	8
4.5. WFATHER	8



1. INTENT

This monthly environmental summary report is a requirement under section 66(6) of the NSW Protection of the Environment Operations Act 1997 (POEO Act), in which holders of an environment protection licence make their pollution monitoring data publicly available. This report is intended to keep the community, stakeholders, and regulators informed of Peak Gold Mine's (PGM's) environmental performance and to maintain a transparent and accountable reporting system.

2. SCOPE

This report covers all of PGMs environmental monitoring conditions covered for August 2018. These conditions, where applicable, are measured against PGMs Environmental Protection Licence (EPL), development consent conditions and Australian Standard to determine PGMs compliance. The conditions include;

- · Blasting monitoring results;
- · Air Quality Monitoring results;
- · Noise Monitoring results;
- Surface Water Monitoring results; and
- · Weather Conditions.

3. DEFINITIONS

mm/s - the peak of the vibration in millimetres per second

Insoluble Solids – the insoluble portion of the dust deposition

Total Lead – Including dissolved lead in the liquid portion and the lead particulates in the filter paper following laboratory analysis

g/m2/month - grams per square meter per month

dB (L) – decibel (linear maximum)

dB LAeq (15 minute) – Decibel (linear weighted average over 15 minutes)

CN Free – Free Cyanide (hydrogen cyanide and cyanide ions in solution)

CN WAD – Weak Acid Dissociable Cyanide (includes cyanide species liberated at moderate pH of 4.5)

TSS - Total Suspended Solids

4. MONITORING RESULTS

4.1. VIBRATION

The vibration monitoring results displayed in Table 4.1a represents all blast vibration events that were trigged at the New Occidental, Fort Bourke and/or Dellavale monitors (Figure 1).

As seen in Table 4.1a all blasting events for the month were below PGMs EPL limits. Vibration limits set by the NSW Environmental Protection Authority (EPA) can be viewed in Table 4.1b.

The compliance against the overall 12-month period will be reported in the EPL Annual Return and Annual Environmental Management Report (AEMR).

Table 4.1a New Occidental, Fort Bourke and Dellavale Vibration Results

Location	Date Sampled & Received	ID	New Occidental (mm/s)	Fort Bourke (mm/s)	Dellavale (mm/s)	Complies (Y/N)
New Cobar	3/08/2018	41StpMainN670	No Trigger	1.103	No Trigger	Υ
New Cobar	13/08/2018	41StpMainN670	No Trigger	2.515	0.857	Υ
New Cobar	21/08/2018	41StpMainN670	No Trigger	3.46	1.461	Υ
New Cobar	27/08/2018	64StpMainN465	0.597	2.831	2.108	Υ
Peak	28/08/2018	8840StpMainN465	0.581	No Trigger	0.632	Υ

Table 4.1b PGM EPL Limits

Peak Particle Velocity (mm/s)	Allowable Exceedance
5.00	<5% of the total number of blasts in a 12 month period are to be below 5mm/s
	511111/3
10.00	NIL





Figure 1: Location of Vibration Monitors on PGM's Mining Leases.

4.2. AIR QUALITY

Fall out dust deposition bottles are currently used to monitor air quality. The bottles are positioned in the field (Figure 2) for a period of 30 \pm 2 days. Monitoring is undertaken quarterly. The bottles are then sent to Australian Laboratory Services (ALS) for external analysis.

PGM has no set limits for air quality monitoring levels. However, takes on board the EPAs best practice limit of 4g/m²/time (limit is applicable to 12 month averaging period). If a single monitoring result is over the EPAs best practice limit of 4g/m²/time, the cause is investigated and reported in the AEMR.

Table 4.2a Dust Monitoring Results

Site	Location	Sampled	Date Obtained	Published	Australia n Standard Limit (g/m2/m onth)	Insoluble Solids (g/m2/m onth)	Total Lead (g/m2/mon th)	Complies
DM1	NW corner of tailings dam	2/7/2018 - 1/8/2018	14/8/2018	19/9/2018	4	0.6	0.00033	Y
DM2	SW corner of tailings dam	2/7/2018 - 1/8/2018	14/8/2018	19/9/2018	4	0.5	0.00006	Y
DM3	Carpark	2/7/2018 - 1/8/2018	14/8/2018	19/9/2018	4	3.3	0.02113	Y
DM4	NE corner of PGM magazine	2/7/2018 - 1/8/2018	14/8/2018	19/9/2018	4	1	0.00073	Y
Bimbimbie	1.2km SW of New Cobar	2/7/2018 - 1/8/2018	14/8/2018	19/9/2018	4	0.8	0.00024	Y



Figure 2: Location of dust gauges on PGM Mining Leases.



4.3. NOISE

A hand-held monitor is used by PGM employees to monitor noise levels at times set out by the EPL and development consent conditions. Noise monitoring is conducted at the closest resident (figure 3) and sporadically depending on operational requirements. PGMs closest monitoring point is located at the Dellavale boundary, approximately 400m closer to the mine noise than the residence. To determine the noise level (dB) experienced at the residence, sound intensity I and the inverse square law $1/r^2$ is calculated based on the residences distance from mine noise source.

Noise monitoring results and licenced noise limits set by the EPL and Development Consent Conditions are given in Table 4.3a respectively.

No Noise Monitoring was undertaken in the month of August.

Time Band	Day	Noise Level (dB)
8:00am - 6:00pm	Mon – Fri	45
6:00pm - 10:00pm	Mon – Fri	40
10:00pm - 8:00am	Mon – Fri	35
8:00am - 1:00pm	Sat	45
1.00pm - 8:00am	Sat	35
12:00am 12:00nm	Sun	25

Table 4.3b Noise Monitoring




Figure 3: Location of the "Dellavale" properties house (blue circle) and noise monitoring location (red diamond).

4.4. WATER

Surface water monitoring involves collecting water samples from a number of locations around site and submitted to external laboratory for physical and chemical analysis, pH and electrical conductivity are obtained using a handheld monitor. Table 4.4 gives the results as per the PGM EPL requirements.

Table 4.4 Water Monitoring Data

Point	Sampled	Received	Published	Limit	WAD CN (mg/L)	CN Free (mg/L)	TSS (mg/L)	Oil & Grease	Complies
Recycled Water Dam	17 (0 (00 10	0.1/0./00.10		No Limit	0.087	0.082	60	*	Yes
End (Peak)	17/8/2018	24/8/2018	19/9/2018						
Raw Water				No	< 0.004	< 0.004	22	*	Yes
Tank (Peak)	17/8/2018	24/8/2018	19/9/2018	Limit					
Spain's Tank				No	*	*	<5	8	Yes
	17/8/2018	24/8/2018	19/9/2018	Limit					
Young	17/8/2018	24/8/2018	19/9/2018	No	*	*	<5	400	Yes
Australia				Limit					

^{*}No monitoring required.

4.5. WEATHER

PGM meteorology monitoring data has been acquired through the Bureau of Meteorology (BOM) weather station located 2km North West of Cobar.

The BOM can be used as an alternate source for this monitoring data.

