



**Peak Gold Mines**  
**MONTHLY ENVIRONMENTAL MONITORING SUMMARY**  
**REPORT**

**EPL 3596**  
**Hillston Road, Cobar**  
**NSW 2835**

**May 2020**



## Contents

1. INTENT .....	3
2. SCOPE .....	3
3. DEFINITIONS .....	3
4. MONITORING RESULTS .....	4
4.1. VIBRATION .....	4
4.2. AIR QUALITY .....	5
4.3. NOISE .....	7
4.4. WATER .....	9
4.5. HAULAGE MOVEMENTS .....	10
4.6. WEATHER .....	11

## 1. INTENT

This monthly environmental summary report is a requirement under section 66(6) of the NSW Protection of the Environment Operations Act 1997 (POEO Act), in which holders of an environment protection licence make their pollution monitoring data publicly available. This report is intended to keep the community, stakeholders, and regulators informed of Peak Gold Mine's (PGM's) environmental performance and to maintain a transparent and accountable reporting system.

## 2. SCOPE

This report covers all of PGMs environmental monitoring conditions covered for May 2020. These conditions, where applicable, are measured against PGMs Environmental Protection Licence (EPL), development consent conditions and Australian Standard to determine PGMs compliance. The conditions include;

- Blasting monitoring results;
- Air Quality Monitoring results;
- Noise Monitoring results;
- Surface Water Monitoring results; and
- Weather Conditions.

## 3. DEFINITIONS

mm/s – the peak of the vibration in millimetres per second

Insoluble Solids – the insoluble portion of the dust deposition

Total Lead – Including dissolved lead in the liquid portion and the lead particulates in the filter paper following laboratory analysis

g/m<sup>2</sup>/month – grams per square meter per month

dB (L) – decibel (linear maximum)

dB LAeq (15 minute) – Decibel (linear weighted average over 15 minutes)

CN Free – Free Cyanide (hydrogen cyanide and cyanide ions in solution)

CN WAD – Weak Acid Dissociable Cyanide (includes cyanide species liberated at moderate pH of 4.5)

TSS – Total Suspended Solids



4. MONITORING RESULTS

4.1. VIBRATION

The vibration monitoring results displayed in Table 4.1a represents all blast vibration events that were triggered at the New Occidental, Fort Bourke and/or Dellavale monitors (Figure 1).

As seen in Table 4.1a all blasting events for the month were below PGMs EPL limits. Vibration limits set by the NSW Environmental Protection Authority (EPA) can be viewed in Table 4.1b.

The compliance against the overall 12-month period will be reported in the EPL Annual Return and Annual Environmental Management Report (AEMR).

Table 4.1a New Occidental, Fort Bourke and Dellavale Vibration Results

Location	Date Sampled & Received	ID	New Occidental (mm/s)	Fort Bourke (mm/s)	Dellavale (mm/s)	Complies (Y/N)
New Cobar	05/05/20	41 NTH 510	No Trigger	1.145	0.59	Y
New Cobar	08/05/20	64 NTH 440	No Trigger	1.341	2.039	Y
Peak	12/05/20	9250 EST 570	No Trigger	No Trigger	No Trigger	Y
Peak	15/05/20	9590 STH 510	No Trigger	No Trigger	No Trigger	Y
Peak	16/05/20	9101 CTL 440	No Trigger	No Trigger	No Trigger	Y
Peak	17/05/20	9300 Fill Pass 2	No Trigger	No Trigger	No Trigger	Y
Peak	20/05/20	9250 EST 570	No Trigger	No Trigger	No Trigger	Y
Peak	22/05/20	9101 CTL 440	No Trigger	No Trigger	No Trigger	Y
New Cobar	23/05/20	441 NTH 510	No Trigger	0.96	No Trigger	Y
Peak	24/05/20	9300 Fill Pass 2	No Trigger	No Trigger	No Trigger	Y
Peak	26/05/20	9590 STH 540	No Trigger	No Trigger	No Trigger	Y
Peak	29/05/20	9101 CTL 440	No Trigger	No Trigger	No Trigger	Y
New Cobar	30/05/20	41 NTH 510	No Trigger	1.303	0.836	Y

Table 4.1b PGM EPL Limits

Peak Particle Velocity (mm/s)	Allowable Exceedance
5.00	<5% of the total number of blasts in a 12 month period are to be below 5mm/s
10.00	NIL



Figure 1: Location of Vibration Monitors on PGM's Mining Leases.

#### 4.2. AIR QUALITY

Fall out dust deposition bottles are currently used to monitor air quality. The bottles are positioned in the field (Figure 2) for a period of  $30 \pm 2$  days. Monitoring is undertaken quarterly. The bottles are then sent to Australian Laboratory Services (ALS) for external analysis.

PGM has no set limits for air quality monitoring levels. However, takes on board the EPA's best practice limit of  $4\text{g}/\text{m}^2/\text{time}$  (limit is applicable to 12 month averaging period). If a single monitoring result is over the EPA's best practice limit of  $4\text{g}/\text{m}^2/\text{time}$ , the cause is investigated and reported in the AEMR.



## MONTHLY ENVIRONMENTAL MONITORING SUMMARY

Table 4.2a Air Quality Results

Site	Location	Date			Australian Standard Limit (g/m <sup>2</sup> /month)	Insoluble Solids (g/m <sup>2</sup> /month)	Total Lead (g/m <sup>2</sup> /month)	Complies
		Sampled	Obtained	Published				
DM1	NW corner of tailings dam	24/04/20-25/05/20	04/06/20	05/06/20	4	0.4	0.000581	Y
DM2	SW corner of tailings dam	24/04/20-25/05/20	04/06/20	05/06/20	4	0.5	0.000228	Y
DM3	Carpark	24/04/20-25/05/20	04/06/20	05/06/20	4	1.8	0.0217	Y
DM4	NE corner of PGM magazine	24/04/20-25/05/20	04/06/20	05/06/20	4	0.3	0.000181	Y
Dellavale	1.3km ESE of New Cobar	24/04/20-25/05/20	04/06/20	05/06/20	4	0.5	0.000197	Y
Bimbimbie	1.2km SW of New Cobar	24/04/20-25/05/20	04/06/20	05/06/20	4	0.8	0.000123	Y




Figure 2: Location of dust gauges on PGM Mining Leases.

#### 4.3. NOISE

A hand-held monitor is used by PGM employees to monitor noise levels at times set out by the EPL and development consent conditions. Noise monitoring is conducted at the closest resident (figure 3) and sporadically depending on operational requirements. PGMs closest monitoring point is located at the Dellavale boundary, approximately 400m closer to the mine noise than the residence. To determine the noise level (dB) experienced at the residence, sound intensity  $I$  and the inverse square law  $1/r^2$  is calculated based on the residences distance from mine noise source.

Noise monitoring results and licenced noise limits set by the EPL and Development Consent Conditions are given in Table 4.3a respectively.



## MONTHLY ENVIRONMENTAL MONITORING SUMMARY

**Table 4.3a Attended Noise Monitoring Results**

Location	Date		Time	LA 10 (dB) Limit	LA 10 (dB) Monitoring Result at Monitor Location	LA 10 (dB) Calculated Monitoring Result at Residence	Key Noise Source	Complies
	Sampled & Obtained	Published						
Dellavale	06/05/2020	27/05/2020	4.45am	35	51.7	47.7	Cars, dump truck on ROM	YES
Dellavale	06/05/20	27/05/20	7.25pm	40	49.1	45.1	Cars, crickets, non-mine truck	YES
Dellavale	26/05/20	27/05/20	8pm	40	49.2	45.2	Cars, non-mine truck	YES
Dellavale	31/05/20	03/06/20	11am	35	42.1	38.1	Birds, mine truck on decline, lots of pigeons	YES

**Table 4.3b Noise Monitoring**

Time Band	Day	Noise Level (dB)
8:00am – 6:00pm	Mon – Fri	45
6:00pm – 10:00pm	Mon – Fri	40
10:00pm – 8:00am	Mon – Fri	35
8:00am – 1:00pm	Sat	45
1:00pm – 8:00am	Sat	35
12:00am – 12:00pm	Sun	35






Figure 3: Location of the “Dellavale” properties house (blue circle) and noise monitoring location (red diamond).

4.4. WATER

Surface water monitoring involves collecting water samples from a number of locations around site and submitted to external laboratory for physical and chemical analysis, pH and electrical conductivity are obtained using a handheld monitor. Table 4.4 gives the results as per the PGM EPL requirements.

Table 4.4 Water Monitoring Data

Point	Sampled	Received	Published	Limit	WAD CN (mg/L)	CN Free (mg/L)	TSS (mg/L)	Oil & Grease	Complies
Recycled Water Dam End (Peak)	05/05/20	14/05/20	28/05/20	No Limit	<0.004	<0.004	131	*	Yes
Raw Water Tank (Peak)	05/05/20	14/05/20	28/05/20	No Limit	<0.004	<0.004	178	*	Yes
Spain’s Tank	05/05/20	14/05/20	28/05/20	No Limit	*	*	<5	<5	Yes
Decant Dam	05/05/20	14/05/20	28/05/20	No Limit	1.91	1.53	86	*	Yes
Young Australia 3	05/05/20	14/05/20	28/05/20	No Limit	*	*	<5	74	Yes



## MONTHLY ENVIRONMENTAL MONITORING SUMMARY

Young Australia 2D	05/05/20	14/05/20	28/05/20	No Limit	*	*	<5	<5	Yes
Young Australia 2C	05/05/20	14/05/20	28/05/20	No Limit	*	*	<5	6	Yes
Young Australia 2B	05/05/20	14/05/20	28/05/20	No Limit	*	*	5	7	Yes
Young Australia 2A	05/05/20	14/05/20	28/05/20	No Limit	*	*	5	14	Yes

\*No monitoring required.

### 4.5. HAULAGE MOVEMENTS

PGM is required to monitor the number of haulage movements undertaken from New Cobar to Peak site as per current consent conditions. A trucking movement includes the travel from New Cobar, to Peak site, return to New Cobar. In the month of May, 775 truck movements were permitted to be undertaken. In total, 462 truckloads were completed. Table 4.5 shows a summary of the trucking movements for the month.

**Table 4.5 Haulage Summary**

Date	Truck Movements
01-05-20	19
02-05-20	16
03-05-20	21
04-05-20	20
05-05-20	20
06-05-20	23
07-05-20	20
08-05-20	0
09-05-20	0
10-05-20	0
11-05-20	20
12-05-20	23
13-05-20	22
14-05-20	41
15-05-20	49
16-05-20	45
17-05-20	43
18-05-20	0
19-05-20	0
20-05-20	0
21-05-20	0
22-05-20	0
23-05-20	0
24-05-20	0

25-05-20	0
26-05-20	7
27-05-20	14
28-05-20	42
29-05-20	17
30-05-20	0
31-05-20	0
<b>Daily Average</b>	<b>14.9</b>

4.6. WEATHER

The meteorology monitoring data has been acquired through PGM's weather station located 2km South of Cobar. Installed in May 2019, the weather station now has enough data for use in the monthly PGM reports.

The BOM website can be used as an alternate source for this monitoring data.

